

## HDL-P 系列防爆边界灯 HDL-P Series Explosion-proof Perimeter Lights



### 应用场所 Application

- ◆ 适用于海洋平台边界指示；
  - ◆ 适用于直升飞机助降信号边界指示；
  - ◆ 适用于爆炸性环境1区，2区，21区，22区等场所；
  - ◆ 适用于环境温度：-40℃~+50℃。
- 
- ◆ Used to indicate the boundary of marine platform;
  - ◆ Used as perimeter light in helicopter landing aid system;
  - ◆ Explosive hazardous atmosphere zone 1, zone2, zone 21, zone22;
  - ◆ Suitable for temperature of -40℃~+50℃.

2

### 产品特性 Features

- ◆ 壳体采用316不锈钢精铸而成，精加工后表面喷塑，防强腐蚀；
  - ◆ 采用优质光学PC透镜，具有阻燃、防紫外线、抗老化等功能；
  - ◆ 采用国际品牌LED光源，寿命长达10万小时；
  - ◆ 内置恒压恒流驱动电源，宽电压输入，恒功率输出，具有启动快，性能稳定，防浪涌、过电流、开路、短路等保护功能；
  - ◆ 体盖结合为迷宫式结构，硅橡胶密封圈，防护等级高；
  - ◆ 专业光学软件设计的二次配光系统，光束分配合理，符合CAP437标准要求；
  - ◆ 内置接线端子，适用于导线： $\leq 3 \times 4.0\text{mm}^2$ ；
  - ◆ 专利产品，仿冒必究。
- 
- ◆ Enclosure is made of 316 stainless steel, powder coated surface after finish machining, with strong corrosion-proof performance;
  - ◆ High quality PC optical lens, with flame retardance, uvoresistant and anti-aging performance;
  - ◆ International brand of LED light source, service life up to 100000 hours;
  - ◆ Built-in constant current constant voltage drive power, wide voltage input, constant power output, with functions of quick start, stable performance, surge-proof, and protection against overcurrent, open circuit, and short circuit etc.;
  - ◆ The joint between lamp body and cover is of labyrinth structure, silicon rubber sealing ring, of high protection degree;
  - ◆ Secondary light distribution system designed by professional optical design software, with reasonable light distribution, conforms to the requirements of CAP437;
  - ◆ Built-in terminal, suitable for conductor:  $\leq 3 \times 4.0\text{mm}$  ;
  - ◆ Patented product, counterfeit will be sued.

Zones 1&2; 21&22

### 选配表 Selection table

| 型号<br>Model | 额定电压(V)<br>Rated voltage | 额定功率(W)<br>Rated power | 防爆标志<br>Ex-Mark                             | 发光颜色<br>Lamp colour | 防护等级<br>Degree of protection | 发光角度<br>Irritation angle | 进线规格<br>Cable entry | 重量(kg)<br>Weight |
|-------------|--------------------------|------------------------|---|---------------------|------------------------------|--------------------------|---------------------|------------------|
| HDL-P8      | 220/230V AC 50/60Hz      | 8                      | Ex d e mb IIC T6 Gb<br>Ex tD A21 IP66 T80°C | 绿色<br>Green         | IP66                         | ±180°                    | 2×M20×1.5           | 4.0              |
| HDL-P8      | 24V DC                   | 6                      |   |                     |                              |                          |                     |                  |
| HDL-P6      | 220/230V AC 50/60Hz      | 6                      |   |                     |                              |                          |                     |                  |
| HDL-P6      | 24V DC                   | 4                      |   |                     |                              |                          |                     |                  |
| HDL-P4      | 220/230V AC 50/60Hz      | 4                      |   |                     |                              |                          |                     |                  |
| HDL-P4      | 24V DC                   |                        |   |                     |                              |                          |                     |                  |

- ◆ 产品出厂时不配防爆格兰，如有需求，订货时请注明；
- ◆ 如需其他特殊要求，订货时请注明。
- ◆ The product is supplied without explosion-proof cable gland. If needed, please specify when ordering;
- ◆ If other special requirements needed, please specify when ordering.

### 外形尺寸 Outline dimension

